



SUPASWIFT

JTP92

Supaswift JTP92

- The rear mounted grass box holds 250 litres and can be emptied without the driver leaving the driving seat.
- A signal indicates when the grass box is full and ready for emptying.
- The Supaswift JTP rider is comfortable to drive, has a small turning circle and cuts close on both sides.
- 92 cm floating cutting deck with central cutting height adjustment. There are 7 cutting heights from 30 - 80 mm.
- Reliable, 15.5 hp Briggs & Stratton Diamond I/C engine with electric start. The petrol tank holds 5.5 litres. All controls are located on an instrument panel. Removable starting key.
- Continuous, hydrostatic gearbox. Cutting speed forward and backwards is regulated by a foot pedal. Brake pedal and parking hand brake.
- Accessories: tow-bar, deflector for cutting high grass without a collection box and front weight.

SUPASWIFT JTP92

MOTOR

Brand Briggs & Stratton Power 15,5hpl/C Cylinders 1 -cyl.

Speed 0 -9 km/h Safety brake Yes Battery 12 V /18 Ah

FUEL

Type of fuel Petrol Tank volume 5,5 litres

SPEED CONTROL

Type of transmission Hydrostatic Number of gears Speed gear 0 -9 km/h + R

STEERING

Type of steering Front wheel steering

WHEELS

Type of wheels Lawn tyre tread

Wheel size Front 13'Rear18"

Bearings Plain

Tyre pressure Front 1,5 bar. Rear 1,2 bar.

Driving Rear wheel drive

CUTTING SYSTEM

Type of cutting system Rear discharge Cutting heights 30 -80 mm in 7 steps.

Cutting width 92 cm Cutting height adjustment Central

CONTROLS

Electric starter Yes Head light Yes Gear lever Foot pedal

MEASURES & WEIGHT

Weight 189 kg Gross weight 231 kg

Package size W*H*L 99 x 105 x 190 cm

Type of package Carton on wooden pallet Units on pallet 1

Largest measures W*H*L 96 x 109 x 219 cm

SEAT

Type of seat Comfort seat Seat adjustable horizontally Yes

OTHER FACTS

CE-mark Yes EAN bar code 731 332 130 146 0 Other GS-mark